



8 Colorways:

SK01-01 White Drift	SK01-05 Shadow
SK01-02 Driftwood	SK01-06 Harvest
SK01-03 Sienna	SK01-07 Copperleaf
SK01-04 Sandstone	SK01-08 Moorland

Designer	Koroseal		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	56.75 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	50 in.
Backing	Woven (Osnaburg)	Nominal Pattern Width	50 in. (127 cm.)
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	<p>NFPA 101® Life Safety Code®</p> <p>NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹ - Class A Rating</p> <p>NFPA 286 Corner Burn Test² - Meets requirements for Flame Spread, Smoke Developed, & Flashover</p> <p><small>1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive</small></p>		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices LINK		
Environmental Product Declaration	LINK		
Health Product Declaration (HPD)	LINK		

For additional technical information please visit koroseal.com

1111 Medina Road | Medina, OH 44256 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2026 Koroseal Interior Products, LLC.