



18 Colorways:	FXW1-01 Strength*	FXW1-07 Dive*	FXW1-13 Essential
	FXW1-02 Breath	FXW1-08 Exhale	FXW1-14 Equilibrium
	FXW1-03 Balance*	FXW1-09 Explore	FXW1-15 Energize*
	FXW1-04 Submerge	FXW1-10 Appraise	FXW1-16 Boost*
	FXW1-05 Hike*	FXW1-11 Retreat	FXW1-17 Optimize*
	FXW1-06 Trek*	FXW1-12 Stability*	FXW1-18 Core*
*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.			

Designer	Koroseal		
Total Weight	20.0 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	52 in.
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating		
	NFPA 286 Corner Burn Test <sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, and Flashover		
	1 When applied to GRC board	2 When applied to 5/8" Type-X-Gypsum board	

CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011
------------------	--

Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices
--------------------	--

For additional technical information please visit [koroseal.com](http://koroseal.com)

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
©2024 Koroseal Interior Products, LLC.