


13 Colorways:

LEM1-01 Meditate*	LEM1-08 Silence
LEM1-02 The Poet*	LEM1-09 Reflection
LEM1-03 The Artist*	LEM1-10 Observation*
LEM1-04 The Inventor*	LEM1-11 Amusement*
LEM1-05 Charisma	LEM1-12 Philosophy*
LEM1-06 Inspiration	LEM1-13 Day Dreamer
LEM1-07 Influence*	

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal		
Total Weight	25.0 oz. ply (774 g. plm.) 16.7 oz. psy (565 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Non-Woven	Nominal Pattern Width	52 in.
Tensile (Minimum)	(212 x 159 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

Fire Testing

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹
 - Class A Rating

NFPA 286 Corner Burn Test²
 - Meets requirements for Flame Spread, Smoke Developed, & Flashover

1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
 ©2024 Koroseal Interior Products, LLC.