



14 Colorways:	67700	47524		
	67701	47528		
	67702	47260		
	67703	47261		
	66704	47264		
	66705	47265		
	47523	47269		
	<hr/>			
Designer	Arte®			
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	N/A	
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A	
Backing	Non-Woven	Nominal Pattern Width	51 in.	
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match	
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II	
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II	
<hr/>				
Fire Testing	NFPA 101® Life Safety Code®			
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating			
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover			
<small>1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive</small>				
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011			
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices			

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
 Arte® is a registered trademark of Arte N.V.
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
 ©2024 Koroseal Interior Products, LLC.