



<b>9 Colorways:</b>	2U22-01 Vellum 2U22-02 Oyster 2U22-05 Coconut	2U22-06 Midnight 2U22-07 Chestnut 2U22-15 Pewter	2U22-16 Birch 2U22-17 Camel 2U22-18 Espresso
<b>Total Weight</b>	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	<b>Vertical Repeat</b>	33 in.
<b>Roll Width</b>	52-54 in. (132-137 cm.)	<b>Horizontal Repeat</b>	52 in.
<b>Backing</b>	Woven (Osnaburg)	<b>Nominal Pattern Width</b>	49.5 in.
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub> (222 x 245 N)	<b>Match Information</b>	Non-Reverse Hang, Straight Match With a 4 in. Drop Match
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub> (111 x 111 N)	<b>WA Spec.</b>	WA-101, Type II
<b>Federal Spec.</b>	CCC-W-408D, Type II	<b>ASTM F-793</b>	Category V, Type II
<b>Fire Testing</b>	NFPA 101® Life Safety Code®  NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating - Flame Spread - 10 - Smoke Developed - 5  NFPA 286 Corner Burn Test <sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, & Flashover  1 When applied to GRC board with A-848-B adhesive    2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
<b>CE Certification</b>	EU classification in accordance with EN 15102:2007 + A1:2011		
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices		

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association  
 ©2023 Koroseal Interior Products, LLC.